CERTIFICATE OF PRODUCT CERTIFICATION

CERTIFICATE NO.: CQC21003314352

Valid from: Sep.08,2022

Valid until:long-term

NAME AND REGISTERED ADDRESS OF THE APPLICANT	NINGBO DORABO ELECTRIC CO.,LTD No. 869, Changxing Road, Changhe Town, Cixi City, Ningbo City, Zhejiang Province
NAME AND REGISTERED ADDRESS OF THE MANUFACTURER	NINGBO DORABO ELECTRIC CO.,LTD No. 869, Changxing Road, Changhe Town, Cixi City, Ningbo City, Zhejiang Province
NAME AND LOCATION OF THE FACTORY	NINGBO DORABO ELECTRIC CO.,LTD No. 869, Changxing Road, Changhe Town, Cixi City, Ningbo City, Zhejiang Province
PRODUCT NAME, MODEL AND SPECIFICATION	Connecting device with screw-type clamping units See appendix
THE STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS	GB/T 13140.1-2008;GB/T 13140.2-2008
TYPE OF CERTIFICATION SCHEMES	Type Testing of Product + Initial Factory Inspection + Follow up Factory Inspection

This is to certify that the above mentioned product(s) complies with the requirements of certification rules of CQC11-462195-2011.

Date of original issued: Sep.26,2021

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body.

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn

SIGNATURE: 谢肇煦

CHINA QUALITY CERTIFICATION CENTRE

CERTIFICATE OF PRODUCT CERTIFICATION

CERTIFICATE NO.：CQC21003314352

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

序号	名称	电压(V)	额定连接容量(mm2)	最高使用环境温度
1	DB910a-b-XXP 其中，XX=2~12，为产品的位数；a=空白/R，代表导电件角度：直针/弯针；b=6.35/7.62/9.52，代表导电件之间的间距：6.35mm/7.62mm/9.52mm；	300	0.5～4.0	T120
2	DB127a-b-XXP 其中，XX=2~12，为产品的位数；a=V/R/A，代表外形及导电件角度：单排直针/单排弯针/双排直针；b=5.0/5.08，代表导电件之间的间距：5.0mm/5.08mm；	300	0.5～1.5	T120
3	DB125a-b-XXP 其中，XX=2~12，为产品的位数；a=空白/H，代表导电件长度：短针/长针；b=3.5/3.81，代表导电件之间的间距：3.5mm/3.81mm；	130	0.5～1.0	T120
4	DB103-b-XXP 其中，XX=2~12，为产品的位数；b=5.0/5.08，代表导电件之间的间距：5.0mm/5.08mm；	300	0.5～2.5	T120
5	DB128a-b-XXP 其中，XX=2~12，为产品的位数；a=V/R，代表导电件角度：直针/弯针；b=5.0/7.5/7.62，代表导电件之间的间距：5.0mm/7.5mm/7.62mm；	300	0.5～2.5	T120
6	DB128a-b-XXP 其中，XX=2~12，为产品的位数；a=L/H，代表导电件长度：短针/长针；b=5.0/5.08，代表导电件之间的间距：5.0mm/5.08mm；			
7	DB129a-b-XXP 其中，XX=2~12，为产品的位数；a=V/R，代表导电件角度：直针/弯针；b=5.0/5.08/7.5/7.62，代表导电件之间的间距：5.0mm/5.08mm/7.5mm/7.62mm；	300	0.5～2.5	T120