

CERTIFICATE OF COMPLIANCE

Certificate Number E484896
Report Reference E484896-20200110
Issue Date 2020-JANUARY-20

Issued to: CIXI DIBO ELECTRONICS CO.,LTD
NO.828 CANGDA ROAD, CHANGHE TOWN
CIXI
ZHEJIANG 315300 CHINA

This is to certify that representative samples of COMPONENT - TERMINAL BLOCKS
SEE ADDENDUM PAGE FOR MODELS

Have been investigated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety: UL1059-Terminal Blocks
CAN/CSA C22.2 No. 158-10- Terminal Blocks

Additional Information: See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Recognized Component Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number E484896
Report Reference E484896-20200110
Issue Date 2020-JANUARY-20

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

USR and CNR Recognized Component - Terminal Blocks

Cat. Nos. DB125, followed by -3.5 or -3.81, followed by -02P thru -99P.

Cat. Nos. DB129, followed by V or R, followed by -5.0 or -5.08 or -7.5 or -7.62, followed by -02P thru -99P.

Cat. Nos. DB2E, followed by KM or KA or KB or KAM or KBM, followed by -3.5 or -3.81, followed by -02P thru -99P.

Cat. Nos. DB2E, followed by KA or KB or KAM or KBM, followed by -5.0 or -5.08 or -7.5 or -7.62, followed by -02P thru -99P.

Cat. Nos. DB2E, followed by RC or RM or VC or VM, followed by -3.5 or -3.81, followed by -02P thru -99P.

Cat. Nos. DB2E, followed by R or RC or RM or V or VC or VM, followed by -5.0 or -5.08 or -7.5 or -7.62, followed by -02P thru -99P.

Cat. Nos. DBT30, followed by C or S or CM or SM, followed by -7.62 or -8.25 or -9.5 or -10.0, followed by -02P thru -99P.

Cat. Nos. DB910, followed by -6.35 or -7.62 or -9.52, followed by -02P thru -99P.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

