

														2		3					4		5			6																																																								
未注公差/General tolerances(mm)														0.1/10 ±2°		REV	ECN	DESCRIPTION		DRFT	DATE																																																													
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500																																																																					
~3	~6	~10	~18	~30	~50	~80	~120	~180	~250	~315	~400	~500																																																																						
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50																																																																					
														DB2EKNNG — 3.5 — XXP — C (Series No.) (Pitch) (Poles) (Color):GN:(Green), BK:(Black), BU:(Blue), RD:(Red), GY:(Gray) OG:(Orange), WT:(White), YL:(Yellow), CR:(Clear)																																																																				
<table><tr><td>UL 标准/UL Standard:</td><td>B</td><td>C</td><td>D</td></tr><tr><td>额定电压/电流/Rated Voltage(V)/Current(A)</td><td>300/8</td><td>/</td><td>/</td></tr><tr><td colspan="4">IEC 标准/IEC Standard:</td></tr><tr><td>过压类别/Overvoltage Category/污染等级/Pollution Degree</td><td>Ⅲ/3</td><td>Ⅲ/2</td><td>Ⅱ/2</td></tr><tr><td>额定电压/电流/Rated Voltage(V)/Current(A)</td><td>160/8</td><td>160/8</td><td>320/8</td></tr><tr><td>额定脉冲电压(KV)/Rate Impulse Voltage(KV)</td><td>2.5</td><td>2.5</td><td>2.5</td></tr><tr><td>线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)</td><td colspan="3">24~16/0.2~1.0,1.5(sol)</td></tr><tr><td>间距/Pitch(mm)/线数范围/Poles</td><td colspan="3">3.50/XX=04~48P</td></tr><tr><td>剥线长度/Stripping length(mm)</td><td colspan="3">8~9</td></tr><tr><td>使用温度范围/Operating temperature(°C)</td><td colspan="3">-40~+105</td></tr><tr><td>符合RoHS环保要求/Conform to RoHS</td><td colspan="3">Yes</td></tr></table>														UL 标准/UL Standard:	B	C	D	额定电压/电流/Rated Voltage(V)/Current(A)	300/8	/	/	IEC 标准/IEC Standard:				过压类别/Overvoltage Category/污染等级/Pollution Degree	Ⅲ/3	Ⅲ/2	Ⅱ/2	额定电压/电流/Rated Voltage(V)/Current(A)	160/8	160/8	320/8	额定脉冲电压(KV)/Rate Impulse Voltage(KV)	2.5	2.5	2.5	线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)	24~16/0.2~1.0,1.5(sol)			间距/Pitch(mm)/线数范围/Poles	3.50/XX=04~48P			剥线长度/Stripping length(mm)	8~9			使用温度范围/Operating temperature(°C)	-40~+105			符合RoHS环保要求/Conform to RoHS	Yes			<table><tr><td>Spring</td><td>Stainless steel</td><td>/</td></tr><tr><td>Conductor</td><td>Copper alloy</td><td>Sn Plated</td></tr><tr><td>Button</td><td>POM</td><td>UL94HB</td></tr><tr><td>Insulator</td><td>PA66</td><td>UL94V-0</td></tr><tr><td>NAME OF PART</td><td>MATERIAL</td><td>NOTES</td></tr></table>										Spring	Stainless steel	/	Conductor	Copper alloy	Sn Plated	Button	POM	UL94HB	Insulator	PA66	UL94V-0	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard:	B	C	D																																																																															
额定电压/电流/Rated Voltage(V)/Current(A)	300/8	/	/																																																																															
IEC 标准/IEC Standard:																																																																																		
过压类别/Overvoltage Category/污染等级/Pollution Degree	Ⅲ/3	Ⅲ/2	Ⅱ/2																																																																															
额定电压/电流/Rated Voltage(V)/Current(A)	160/8	160/8	320/8																																																																															
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	2.5	2.5	2.5																																																																															
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)	24~16/0.2~1.0,1.5(sol)																																																																																	
间距/Pitch(mm)/线数范围/Poles	3.50/XX=04~48P																																																																																	
剥线长度/Stripping length(mm)	8~9																																																																																	
使用温度范围/Operating temperature(°C)	-40~+105																																																																																	
符合RoHS环保要求/Conform to RoHS	Yes																																																																																	
Spring	Stainless steel	/																																																																																
Conductor	Copper alloy	Sn Plated																																																																																
Button	POM	UL94HB																																																																																
Insulator	PA66	UL94V-0																																																																																
NAME OF PART	MATERIAL	NOTES																																																																																
<table><tr><td>MAT NO.:</td><td colspan="2">/</td><td colspan="2" rowspan="2"> 宁波地博电气有限公司 NINGBO DORABO ELECTRICAL CO., LTD </td></tr><tr><td>STATUS:</td><td colspan="2">/</td></tr><tr><td>APPD: Steven Lu</td><td colspan="2">2025.11.19</td><td colspan="2">NAME:</td><td colspan="2">DB2EKNNG-3.5-XXP-C</td></tr><tr><td>CHKD: Jting Chen</td><td colspan="2">2025.11.19</td><td colspan="2">DRAWING NO.:</td><td colspan="2">/</td></tr><tr><td>DRFT: Tom Mao</td><td colspan="2">2025.11.19</td><td colspan="2">REV</td><td colspan="2">TO</td></tr><tr><td>SIZE: A4</td><td colspan="2">mm (inch)</td><td colspan="2">TYPE: CUSTOMER DRAWING</td><td colspan="2">SCALE: SHEET 1/1</td></tr></table>														MAT NO.:	/		宁波地博电气有限公司 NINGBO DORABO ELECTRICAL CO., LTD		STATUS:	/		APPD: Steven Lu	2025.11.19		NAME:		DB2EKNNG-3.5-XXP-C		CHKD: Jting Chen	2025.11.19		DRAWING NO.:		/		DRFT: Tom Mao	2025.11.19		REV		TO		SIZE: A4	mm (inch)		TYPE: CUSTOMER DRAWING		SCALE: SHEET 1/1																																		
MAT NO.:	/		宁波地博电气有限公司 NINGBO DORABO ELECTRICAL CO., LTD																																																																															
STATUS:	/																																																																																	
APPD: Steven Lu	2025.11.19		NAME:		DB2EKNNG-3.5-XXP-C																																																																													
CHKD: Jting Chen	2025.11.19		DRAWING NO.:		/																																																																													
DRFT: Tom Mao	2025.11.19		REV		TO																																																																													
SIZE: A4	mm (inch)		TYPE: CUSTOMER DRAWING		SCALE: SHEET 1/1																																																																													