

														2										3										4										5										6																																									
未注公差/General tolerances(mm)														0.1/10 ±2°										REV		ECN		DESCRIPTION						DRFT		DATE																																																											
0		>3		>6		>10		>18		>30		>50												>80		>120		>180		>250		>315		>400		>500																																																											
~3		~6		~10		~18		~30		~50		~80												~120		~180		~250		~315		~400		~500																																																													
±0.12		±0.18		±0.22		±0.26		±0.31		±0.37		±0.57		±0.80		±0.93		±1.05		±1.15		±1.60		±2.20		±2.50																																																																					
														DB2EKNM — 3.5 — XXP — C (Series No.) (Pitch) (Poles) (Color):GN:(Green), BK:(Black), BU:(Blue), RD:(Red), GY:(Gray) OG:(Orange), WT:(White), YL:(Yellow), CR:(Clear)																																																																																	
<table><tr><td>UL 标准/UL Standard:</td><td>B</td><td>C</td><td>D</td></tr><tr><td>额定电压/电流/Rated Voltage(V)/Current(A)</td><td>300/8</td><td>/</td><td>/</td></tr><tr><td colspan="4">IEC 标准/IEC Standard:</td></tr><tr><td>过压类别/Overvoltage Category/污染等级/Pollution Degree</td><td>Ⅲ/3</td><td>Ⅲ/2</td><td>Ⅱ/2</td></tr><tr><td>额定电压/电流/Rated Voltage(V)/Current(A)</td><td>160/8</td><td>160/8</td><td>320/8</td></tr><tr><td>额定脉冲电压(KV)/Rate Impulse Voltage(KV)</td><td>2.5</td><td>2.5</td><td>2.5</td></tr><tr><td>线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)</td><td colspan="3">24~16/0.2~1.0,1.5(sol)</td></tr><tr><td>间距/Pitch(mm)/线数范围/Poles</td><td colspan="3">3.50/XX=04~48P</td></tr><tr><td>剥线长度/Stripping length(mm)</td><td colspan="3">8~9</td></tr><tr><td>使用温度范围/Operating temperature(°C)</td><td colspan="3">-40~+105</td></tr><tr><td>符合RoHS环保要求/Conform to RoHS</td><td colspan="3">Yes</td></tr></table>														UL 标准/UL Standard:	B	C	D	额定电压/电流/Rated Voltage(V)/Current(A)	300/8	/	/	IEC 标准/IEC Standard:				过压类别/Overvoltage Category/污染等级/Pollution Degree	Ⅲ/3	Ⅲ/2	Ⅱ/2	额定电压/电流/Rated Voltage(V)/Current(A)	160/8	160/8	320/8	额定脉冲电压(KV)/Rate Impulse Voltage(KV)	2.5	2.5	2.5	线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)	24~16/0.2~1.0,1.5(sol)			间距/Pitch(mm)/线数范围/Poles	3.50/XX=04~48P			剥线长度/Stripping length(mm)	8~9			使用温度范围/Operating temperature(°C)	-40~+105			符合RoHS环保要求/Conform to RoHS	Yes													<table><tr><td>Screw</td><td>Steel</td><td>Zn Plated</td></tr><tr><td>Spring</td><td>Stainless steel</td><td>/</td></tr><tr><td>Conductor</td><td>Copper alloy</td><td>Sn Plated</td></tr><tr><td>Button</td><td>POM</td><td>UL94HB</td></tr><tr><td>Insulator</td><td>PA66</td><td>UL94V-0</td></tr><tr><td>NAME OF PART</td><td>MATERIAL</td><td>NOTES</td></tr></table>										Screw	Steel	Zn Plated	Spring	Stainless steel	/	Conductor	Copper alloy	Sn Plated	Button	POM	UL94HB	Insulator	PA66	UL94V-0	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard:	B	C	D																																																																																												
额定电压/电流/Rated Voltage(V)/Current(A)	300/8	/	/																																																																																												
IEC 标准/IEC Standard:																																																																																															
过压类别/Overvoltage Category/污染等级/Pollution Degree	Ⅲ/3	Ⅲ/2	Ⅱ/2																																																																																												
额定电压/电流/Rated Voltage(V)/Current(A)	160/8	160/8	320/8																																																																																												
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	2.5	2.5	2.5																																																																																												
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)	24~16/0.2~1.0,1.5(sol)																																																																																														
间距/Pitch(mm)/线数范围/Poles	3.50/XX=04~48P																																																																																														
剥线长度/Stripping length(mm)	8~9																																																																																														
使用温度范围/Operating temperature(°C)	-40~+105																																																																																														
符合RoHS环保要求/Conform to RoHS	Yes																																																																																														
Screw	Steel	Zn Plated																																																																																													
Spring	Stainless steel	/																																																																																													
Conductor	Copper alloy	Sn Plated																																																																																													
Button	POM	UL94HB																																																																																													
Insulator	PA66	UL94V-0																																																																																													
NAME OF PART	MATERIAL	NOTES																																																																																													
<table><tr><td>MAT NO.:</td><td colspan="3">/</td></tr><tr><td>STATUS:</td><td colspan="3">/</td></tr><tr><td>APPD: Steven Lu</td><td colspan="3">2025.11.20</td></tr><tr><td>CHKD: Jting Chen</td><td colspan="3">2025.11.20</td></tr><tr><td>DRFT: Tom Mao</td><td colspan="3">2025.11.20</td></tr><tr><td>SIZE: A4</td><td colspan="3">mm (inch)</td></tr></table>														MAT NO.:	/			STATUS:	/			APPD: Steven Lu	2025.11.20			CHKD: Jting Chen	2025.11.20			DRFT: Tom Mao	2025.11.20			SIZE: A4	mm (inch)			ORABO NINGBO DORABO ELECTRICAL CO., LTD NAME: DB2EKNM-3.5-XXP-C DRAWING NO.: / TYPE: CUSTOMER DRAWING SCALE:										<table><tr><td>REV</td><td colspan="2">TO</td></tr><tr><td>SHEET</td><td colspan="2">1/1</td></tr></table>										REV	TO		SHEET	1/1																																	
MAT NO.:	/																																																																																														
STATUS:	/																																																																																														
APPD: Steven Lu	2025.11.20																																																																																														
CHKD: Jting Chen	2025.11.20																																																																																														
DRFT: Tom Mao	2025.11.20																																																																																														
SIZE: A4	mm (inch)																																																																																														
REV	TO																																																																																														
SHEET	1/1																																																																																														