

	linear dimension(Tolerances Standard GB/T 14486-2008)							— ∕ ⊥			REV		ECN	DESCRIPTION		DRFT	DATE		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	to 10	over 10 to 100	over 100 to										
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60									

UL/CUL 技术 参数 UL/CUL Technical Data									
等级	Use Group	B	C	D					
额定电压	Rated Voltage [V]	300	-	300					
额定电流	Rated Current [A]	9	-	10					
接线范围	Wire Range								
单/多芯线	Solid/Stranded [AWG]								
耐电压	Withstanding Voltage				1600V/1Min				
IEC 技术参数 IEC Technical Data									
过电压类别	Overvoltage Category	III	III	II					
污染等级	Contamination Class	3	2	2					
额定电压	Rated Voltage [V]	160	160	320					
额定电流	Rated Current [A]	9	9	9					
额定冲击电压	Impulse withstand voltagea [KV]	4.0	4.0	4.0					
导线截面积	Conductor cross section				1.5				
硬质/柔性导线	Solid/ flexible [mm²]								
一般参数 Other Data									
间距 Pitch	[mm]				4.0				
极数 Poles	[P]				01~03				
剥线长度 Stripping Length	[mm]				-				
螺丝 Screw/扭矩 Torque(Max)	[N.m]				-				
工作温度 Operating temperatur	[°C]				-40~+105				
引针尺寸 Pin Dimensions	[mm]				1.0				
PCB板孔径 PCB Hole Diameter	[mm]				-				

DB2062V — 4.0 — XXP — C

(Series No.) (Pitch) (Poles)

(Color):GN:(Green), BK:(Black), BU:(Blue), RD:(Red), GY:(Gray) OG:(Orange), WT:(White), YL:(Yellow), CR:(Clear)

APPD:	JTing Chen	2024.03.04	NAME:		DB2062V-4.0-XXP-C		
CHKD:	Duck Mao	2024.03.04	DRAWING NO.:		/	REV	M0
DRFT:	Steven Lu	2024.03.04	TYPE:		CUSTOMER_DRAWING	SCALE:	SHEET
		SIZE:A4			1/1		